

FLANGER 1.6



Turn up the power and automatically follow any edge—straight or curved.

The FLANGER 1.6 automatically follows any edge—curved or straight. Use the convenient table slot to turn up a “starting flange” and let it go! A calibrated dial can be set for radii as small as 3-1/8” (2” when auto-guide is deactivated). Machine can be set to produce either of two flange heights—approximately 3/8” (9.5 mm) or 1/4” (6.4 mm). A non-releasing type head is suitable for open end fittings, straight and irregular curves. Automatically flange 16 to 24-gauge (.55 mm or 1.61 mm) material at speeds of 18 fpm (5.5 m/min).

Standard with JAG quality construction, this machine has an industrial motor; heavy 3/4” (19mm) chassis plate; and an arc-welded steel stand protected with top-quality primer and paint finish.



SPECIFICATIONS

Capacity:	16 – 24 gauge (0.55 – 1.61 mm)
Depth of Pocket:	3/8” (9.5 mm) or 1/4” (6.4 mm)
Speed:	18 fpm (5.5 m/min)
Motor:	2 HP (1.5 kw) – 115/230 volts, 60 cycle, single phase, AC, 1800 RPM
Dimensions:	26”L x 24W” x 38”H (660 x 610 x 965 mm)
Weight:	300 lbs. (136 kg)

Contact Us Today! ■ 262-408-3870 ■ jag-machinery.com ■ sales@jag-machinery.com

JAG SHEET METAL MACHINERY, LLC