

# AIR FOLDER



## A free standing general fabrication wrap brake.

The AIR FOLDER is ideal for forming and bending panels and other flanged metal parts.

- Pneumatic operated, foot pedal control.
- Rugged welded steel construction.
- Maintenance-free bearing and guides.
- Pneumatic drive folding beam.
- Safety interlock controls.
- Dial-adjustable bend angle 0-90°.
- Automatic TDC/F notch locator.
- Pneumatic drive clamping beam with automatic return.



## SPECIFICATIONS

Capacity:	24 - 16 gauge (0.70 - 1.6 mm)
Depth of Pocket:	1/2" (12.7 mm) – uses 1-3/8" (34.9 mm) of material
Maximum Bend Length:	60" (1525 mm)
Maximum Galvanized Steel Thickness:	1/16" (1.6 mm)
Minimum Wrap Duct Size:	8.7" x 8.7" (220 x 220 mm)
Clean, Dry Air Supply:	11 CFM at 100 PSI (not to exceed 120 PSI)
Dimensions:	88"L x 46"W" x 35"H (2235 x 1170 x 890 mm)
Weight:	2,046 lbs. (930 kg)

Contact Us Today! • 262-408-3870 • [jag-machinery.com](http://jag-machinery.com) • [sales@jag-machinery.com](mailto:sales@jag-machinery.com)

JAG SHEET METAL MACHINERY, LLC